

नागरिक सहकारी बैंक मर्यादित ग्वालियर

(म.प्र. सहकारी सोसाइटी अधिनियम 1960 के अधीन रजिस्ट्रीकृत)

प्रधान कार्यालय : 73, गोविन्दपुरी, विश्वविद्यालय मार्ग, ग्वालियर - 474 011

पत्र क्रिक्लय / 2024-2025 / 46 / 123

दिनांक :

16-05-2024

निविदा / कोटेशन आमंत्रण सूचना

मेसर्स	

प्रिय / महोदय नागरिक सहकारी बैंक मर्यादित ग्वालियर की शाखा-मालरोड मुरार, ग्वालियर हेतु फायर अलार्म ,

सिक्यूरिटी अलार्म , सी.सी.टी.व्ही. कैमरा नीचे दी गयी तालिका अनुसार कृय किये जाने हेतु कोटेशन आमंत्रित किये जा रहे है। अन्य जानकारी बैंक प्रधान कार्यालय-गोविंदपुरी ग्वालियर से प्राप्त की जा सकती है। कृपया कोटेशन दिनांक 21.05.2023 तक सील बंद लिफाफें में प्रबंध संचालक / महाप्रबंधक नागरिक सहकारी बैंक मर्यादित ग्वालियर प्रधान कार्यालय 73 गोविन्दपुरी विश्वविद्यालय मार्ग ग्वालियर के नाम से अथवा ई मेल आई NSBCORE@NSBGWALIOR.COM पर निर्धारित प्रारूप ,प्रपत्र सहित प्राप्त हो जाने चाहिये । विलम्व से प्राप्त होने वालें कोटेशन पर विचार नहीं किया जावेगा --:

सं.	सामग्री	समग्री का विवरण	नग
क .			संख्या
1	FIRE ALARM SYSTEM	Fire panel: Providing, fixing, testing &commissioning microprocessor based main fire alarm panel and indicating panel solid state modular card type pulsar, timer for dual stage alarm facility with indicators, standby battery ,complies to IS 2189:1999.2 x 16 character backlit LCD display lamp test features. Complete with integral power supply and battery charger for SMF battery. NO/NC contacts for both fire and fault. Switches to enable on board operation. LCD and LED Indication for open, short circuit, Isolate, fire in each zone. reset, lamp test, silence, isolate, short, open, fire continuous buzzer for fault and intermittent buzzer for fire battery charger box, operating voltage 220 Volt mains A.C. input/24V D.C. output etc. complete in all respect. 2 zone fire panel (SOR 50.1)	1
6		Smoke detector (ionization type): Providing &fixing of ionization type smoke detectors as per IS: 11360-1985 of dual chamber, 12/24 volt DC, ionization source-less than one micro curie maximum Americium 241, twin visual alarm indicator (LED's) "Blink" in stand by and "steady" in alarm complete in all respects. (SOR 50.2)	8
		Heat detector: providing & fixing of heat detector based on heat rate- ofrise/fixed temperature with working voltage 9-33V DC twin visual alarm indicator (LED's) "Blink" in stand by and "steady" in alarm complete in all respects. (SOR 50.4)	7
		Manual call point- providing and fixing of manual calls point flush or surface mounting, front protection glass cover. Unbreakable glass	3
中部		Internal hooter: Providing &fixing of internal hooter with working AC Voltage 220V A.C./24V D.C. current consumption, sound output 120 DB, material M.S. sheet. (SOR 50.8)	2
COA !		a). 2 C X 1.5 sqmm. Power cable & RG 6 Cablein conduit pipe.	102 RM
CHOP!	<u></u>		क्रमशः

02

फोन: 0751-2371603, 4923201

email: nsbho@nsbgwalior.com • website: www.nsbgwalior.com



नागरिक सहकारी बैंक मर्यादित ग्वालियर

(म.प्र. सहकारी सोसाइटी अधिनियम 1960 के अधीन रजिस्ट्रीकृत)

प्रधान कार्यालय : 73, गोविन्दपुरी, विश्वविद्यालय मार्ग, ग्वालियर - 474 011

^{पत्र क्रमांक :} मुख्यालय / 2024—2025 / 46 / 123

दिनांक :

16-05-2024

-2-

-			
		Fire Extinguishers- supplying and fixing of fire extinguisher/ Refuills as	3
		per IS	
		specifications - duly filled 6kg and ready to use. (SOR 42.77.1) SUPPLY& FIXING OF TWO CORE FRLS CABLE 1.5 SQ. MM WIRE IN	DIA.
			90 RMt
		CONDUIT PIPE	
	Security	Security Alarm panel- SUPPLY& FIXING OF 4-ZONE, PANAL-MAKE-	1
	Alarm-:	(AGNI,AGNISURAKSHA	
2		PIR SENSOR- Supply, installation, testing and commissioning of 230 V	1
		AC operated movement detector shall have an operating range of	
		96253V AC with 1 NO, 10 A, AgSnO2 contact material with starting	
		current of 100Aand shall have universal mounting position to permit the	
		selection of any area of survey with IP 40 protection. It shall have an	
		ambient temperature range of - 30 to +50 deg C. The movement	
		detector shall have a dielectric strength between open contacts	
	•	of 1000V AC with an electrical life at rated load AC1 of 1 lakh cycles	
		with necessary approvals like CE, EAC and IMQ (SOR- 52.4.1)	
		SUPPLY& FIXING OF MAGNETIC SWITCH-MAKE-	1
		(AGNI,AGNISURAKSHA)	
		SUPPLY& FIXING OF PANIC SWITCH-MAKE-	5
		(AGNI,AGNISURAKSHA)	
		providing and fixing Battery 12 V, 7 AH of excide make for security	1
		alarm system of AGNI make as per architect's instruction	
		providing and fixing Battery 12 V, 7 AH of excide make for fire alarm	2
		system of AGNI make as per architect's instruction	_
	C C MI	16 channel NVR with 1 SATA- Supply, installation testing and	1
3	C.C. TV	commissioning of 16ch network video recorder with real-time recording:	
	Cabling	up to 4 MP resolution live view, preview and playback/up to 16 channels	
		at 1080p, with inbuilt PoE, up to 1TB supports complete with UL	
		at 1000p, with inbuilt FOE, up to 11B supports complete with OE	
		contification	
		certification	
		(SOR-54.19)	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-	9
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely	9
	¥	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1)	
	¥	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1)	9
	v	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression :- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera	
	v	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression :- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to	
	v	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression :- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6	
	v	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression :- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night	
	v	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98	
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR, backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12	
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:-BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with	
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight	
	2	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely	
	· ·	(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight	
		(SOR-54.19) 2 MP IP IR eyeball camera with H.264 video compression Supply, Installation testing and commissioning of the IP dome camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely adjustable (SOR 54.1) 2 MP IP IR bullet camera with H.264 Video compression Supply, Installation testing and commissioning of the IP bullet camera shall be equipped with a 1/2.8 2 MP progressive scan CMOS imager to capture full HD 1080p (25/30 fps) images, a 3.6 mm fixed lens, and a waterproof (IP66) enclosure. As a true day/night solution, the camera shall use smart IR technology and provide up to 98 ft (30 m) of IR illumination. The camera shall accept PoE (802.3af) or 12 V DC power input. min. illumination:-0.1 lux @F1.2, AGC ON, 0 lux with IR video compression:- H.264, noise reduction: 3DNR,backlight compensation:- BLC/HLC/DWDR, encode mode:- CBR/VBR (freely	



कमशः-०३

फोन : 0751-2371603, 4923201

email: nsbho@nsbgwalior.com • website: www.nsbgwalior.com

F:\New folder\Work-Order-8-Servic_Letter_SATENDRA_SHARMA.doc.docx



नागरिक सहकारी बैंक मर्यादित ग्वालियर

(म.प्र. सहकारी सोसाइटी अधिनियम 1960 के अधीन रजिस्ट्रीकृत)

प्रधान कार्यालय : 73, गोविन्दपुरी, विश्वविद्यालय मार्ग, ग्वालियर - 474 011

पत्र क्रमांक : मुख्यालय / 2024—2025 / 46 / 123

दिनांक:

16-05-2024

-3-

Cable- Supplying and drawing 4 pair shielded twisted pair (STP), 0.5 mm PVC insulated copper conductor un-armoured Cat-6 computer	260M
cable FRLS in existing surface/concealed, steel/PVC. conduit/ casing-n-capping as required. (SOR 38.12)	Я
8 port PoE switch with 2 SFP ports- Supply, installation testing and commissioning of 8 port PoE switch with 2 SFP ports, having security features like port security supports 64 MACs per port, auto surveillance VLAN, loopback detection automatically disables a port when a loop is detected, cable diagnostics allows administrators to determine cable status, UTP cat. 5, cat. 5e (100 m max.), full/halfduplex for 10/100 MBPS, fullduplex for 1000 MBPS, auto MDI/MDIX adjustment for all twisted-pair ports, switching capacity, 40 GBPS, maximum 64 bytes packet forwarding rate, 14.88 MBPS, ports 1 to 8 compliant with 802.3at (SOR-54.27.1)	2
providing and fixing NVR box as per architect's instruction	1
CCTV colour monitor- Supply, installation, testing and commissioning of 32" flat LED colour monitors.(SOR-54.31.1)	1

निविदा के साथ आपको निम्नानुसार जानकारी प्रस्तुत करनी होगी -:

- (1) कार्य दक्षता का प्रमाण पत्र
- (2) फर्म का जी.एस.टी. एवं अन्य पंजीयन
- (3) फर्म का पेन नम्बर
- (4) कम्पनी की प्रोफाइल ,
- (5) Terms Conditions
- (6) Service Level Agreement

नोट – किसी भी प्रस्ताव को मान्य करने अथवा अमान्य करने का अंतिम अधिकार बैंक प्रबंधन को होगा।



महाप्रबंधक् (\

नागरिक सहकारी बैंक मर्यादित ग्वालियर प्रधान कार्यालय 73,गोविन्दपुरी,विश्वविद्यालय मार्ग,ग्वालियर

फोन: 0751-2371603, 4923201

email: nsbho@nsbgwalior.com • website: www.nsbgwalior.com

F:\new folder\Work-Order-&-Servic_Letter_SATENDRA_SHARMA.doc.doc